

LIMESTONE (Less than 1% Silica)

SDS Number: USA-002

Revision Date: 2/26/2021

Page 1 of 5

1 **PRODUCT AND COMPANY IDENTIFICATION**

Manufacturer

U.S. Aggregates, Inc.
5400 West 86th Street
Indianapolis, Indiana 46268

Vendor

U.S. Aggregates, Inc.
5400 West 86th Street
Indianapolis, Indiana 46268

Emergency: Laurie Webb: 317-767-4694 (cell)
Contact: Laurie Webb
Phone: 317-874-4928
Fax: 317-875-4673
Email: lwebb1@usagg.com
Web: www.usagg.com

Emergency: Laurie Webb: 317-767-4694 (cell)
Contact: Laurie Webb
Phone: 317-874-4928
Fax: 317-875-4673
Email: lwebb1@usagg.com
Web: www.usagg.com

Product Name: LIMESTONE (Less than 1% Silica)
Revision Date: 2/26/2021
SDS Number: USA-002
Common Name: Limestone, Including Dolomite
CAS Number: 1317-65-3
Chemical Family: Calcium and Magnesium Carbonate
Chemical Formula: CaCO3 and MgCO3
Synonyms: Aggregate, Agricultural Lime, AgLime, Fine Lime, Glass Stone, Crushed Stone, Manufactured Sand, Mineral Filler
Product Use: This Safety Data Sheet applies to natural crushed limestone products originating from the U.S. Aggregates quarries located at:
Delphi, Indiana
Francesville, Indiana
Lowell, Indiana
Monon, Indiana
Pleasant Mills, Indiana
Portland, Indiana (for fine lime and fine grind glass stone)
Springville, Indiana

2 **HAZARDS IDENTIFICATION**

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

Health, Specific target organ toxicity - Single exposure, 3
Health, Acute toxicity, 5 Inhalation

GHS Label elements, including precautionary statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:



GHS Hazard Statements:

H335 - May cause respiratory irritation
H333 - May be harmful if inhaled

GHS Precautionary Statements:

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

LIMESTONE (Less than 1% Silica)

SDS Number: USA-002

Revision Date: 2/26/2021

Page 2 of 5

Hazards not otherwise classified (HNOC) or not covered by GHS

Route of Entry: Inhalation
Target Organs: Respiratory system
Inhalation: Inhaling respirable dust may aggravate existing respiratory system disease(s) and/or dysfunctions.

RESPIRABLE CRYSTALLINE SILICA (QUARTZ):

This limestone may contain an amount of respirable crystalline silica.

ACGIH TLV: 0.05 mg/m³
 MSHA and OSHA PEL: 10/(%SiO₂ + 2) mg/m³
 MSHA and OSHA proposed PEL: 0.1 mg/m³

WARNING

AVOID BREATHING DUST FROM THIS PRODUCT

This product contains crystalline silica. Prolonged and repeated breathing of crystalline silica dust can cause a progressive lung disease called silicosis.

Also, some researchers have reported that there is evidence that prolonged and repeated breathing of crystalline silica dust may cause lung cancer.

Either silicosis or lung cancer can result in permanent injury or death.

Skin Contact: Exposure to dust may aggravate skin conditions.

Eye Contact: Exposure to dust may aggravate eye conditions or cause irritation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
1317-65-3	1-98%	Calcium carbonate
546-93-0	1-98%	Magnesite
14808-60-7	<1%	Silica, crystalline

Magnesite is also known as Magnesium Carbonate.

Component ranges all vary naturally.

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Control dusts in workplace.
Skin Contact: Dust in previously irritated skin should be washed with soap and water. Contact a physician if irritation persists.
Eye Contact: Flush eyes with running water for 15 minutes. Contact a physician if irritation persists.
Ingestion: Relatively non-toxic in small quantities. Contact a physician if a problem arises.

5 FIRE FIGHTING MEASURES

Flammability: Non-flammable inert material.

6 ACCIDENTAL RELEASE MEASURES

Spilled material should not cause any environmental harm except that respirable dust may be generated. Consider the use of wetting or other air emission controls to control the generation and exposure to dust.

LIMESTONE (Less than 1% Silica)

SDS Number: USA-002

Revision Date: 2/26/2021

Page 3 of 5

7	HANDLING AND STORAGE
----------	-----------------------------

Handling Precautions: Respirable dust may be generated during processing, handling, and storage. Engineering controls such as wetting, dust suppression, ventilation, process enclosure, enclosed employee work stations, etc. should be used to keep dust emissions below the appropriate PEL. Respirable dust levels should be monitored regularly.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
----------	--

Engineering Controls: Local exhaust or general ventilation adequate to maintain exposures below appropriate PELs.

Personal Protective Equipment:

Eye/Face Protection: Safety glasses with sideshields should be worn as minimum protection. Dust goggles should be worn when excessively (visible) dusty conditions are present or anticipated.

Skin Protection: Cloth gloves are acceptable.

Respiratory Protection: NIOSH/MSHA-approved dust respirators for conditions where dust levels exceed or are likely to exceed appropriate exposure limits. Respirator use must comply with applicable MSHA or OSHA standards, which include provisions for a user training program, respirator repair and cleaning, respirator use medical clearance, fit testing, and other requirements.

Work/Hygienic Practices: Wash clothes after each use. Wash dust-exposed skin with soap and water.

CALCIUM CARBONATE, MAGNESIUM CARBONATE:

ACGIH TLV: 10 mg/m³ (total dust)
 OSHA PEL: 15 mg/m³ (total dust, 5 mg/m³ (respirable fraction))

RESPIRABLE CRYSTALLINE SILICA (QUARTZ):

This limestone may contain an amount of respirable crystalline silica.

ACGIH TLV: 0.05 mg/m³
 MSHA and OSHA PEL: 10/(%SiO₂ + 2) mg/m³
 MSHA and OSHA proposed PEL: 0.1 mg/m³

9	PHYSICAL AND CHEMICAL PROPERTIES
----------	---

Appearance:	Angular gray, white, or tan particles in size from powder to boulders.	Odor:	None
Physical State:	Solid	Molecular Formula:	CaCO ₃ and MgCO ₃
Spec Grav./Density:	2.5 - 2.8	Solubility:	Insoluble in water
pH:	8 - 10	Percent Volatile:	Zero
Molecular weight:	100.09		

10	STABILITY AND REACTIVITY
-----------	---------------------------------

Materials to Avoid: Strong acids will dissolve limestone by neutralization. Contact with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trifluoride, and oxygen difluoride may cause fire and/or explosion of the released gas.

Hazardous Decomposition: Silica dissolves in hydrofluoric acid producing a corrosive gas - silicon tetrafluoride.

Hazardous Polymerization: Will not occur.

LIMESTONE (Less than 1% Silica)

SDS Number: USA-002

Revision Date: 2/26/2021

Page 4 of 5

11	TOXICOLOGICAL INFORMATION
-----------	----------------------------------

In October 1996, an IARC working group reassessing crystalline silica, a component of this product, designated crystalline silica as a carcinogen. (Group 1).

Chronic exposure to respirable quartz containing limestone dust in excess of appropriate PELs has caused silicosis, a progressive pneumoconiosis. Not all individuals with silicosis will exhibit symptoms or signs of the disease. However, silicosis is progressive, and symptoms can appear at any time, even years after exposures have ceased. Symptoms of silicosis may include (but not limited to): shortness of breath, reduction in lung volume, right heart enlargement and/or failure. Persons with silicosis have an increased risk of pulmonary tuberculosis infection. Crystalline silica, a component of this product, has been designated by IARC as Group 1, a substance known to cause cancer in humans.

Limestone is not listed as a carcinogen on the NTP, IARC, or OSHA lists of carcinogens.

12	ECOLOGICAL INFORMATION
-----------	-------------------------------

This product is not known to harm wildlife, aquatic life, or the environment.

13	DISPOSAL CONSIDERATIONS
-----------	--------------------------------

Unless contaminated by other materials, no regulations are applicable to disposing or otherwise moving this product.

RCRA Information:

This material, if discarded as produced, is not a RCRA "listed" hazardous waste. Use which results in chemical or physical change or contamination may subject it to regulation as a hazardous waste. It is the responsibility of the generator to fully characterize for toxicity and other RCRA parameters prior to disposal (40 CFR 261). Along with properly characterizing all waste materials, consult state and local regulations regarding proper disposal of this material.

14	TRANSPORT INFORMATION
-----------	------------------------------

This product is not a hazardous material as defined by the U.S. Department of Transportation.

15	REGULATORY INFORMATION
-----------	-------------------------------

Component (CAS#) [%] - CODES

 Calcium carbonate (1317-65-3) [1-98%] MASS, OSHAWAC, PA, TSCA, TXAIR

Magnesite (546-93-0) [1-98%] MASS, OSHAWAC, TSCA, TXAIR

Silica, crystalline (14808-60-7) [1-5%] MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

Regulatory CODE Descriptions

- MASS = MA Massachusetts Hazardous Substances List
 OSHAWAC = OSHA Workplace Air Contaminants
 PA = PA Right-To-Know List of Hazardous Substances
 TSCA = Toxic Substances Control Act
 TXAIR = TX Air Contaminants with Health Effects Screening Level
 NRC = Nationally Recognized Carcinogens

LIMESTONE (Less than 1% Silica)

SDS Number: USA-002

Revision Date: 2/26/2021

Page 5 of 5

16

OTHER INFORMATION

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

U.S. Aggregates, Inc.